

CLG

油壓順序閥 (日式規格)

CLG HYDRAULIC SEQUENCE VALVE (JAPAN SPECIFICATION)



注意事項

1次側供油量過多有時會導致不能準備的進行順序動作。請在1次側油孔前面安裝內置有單向閥的流量調節閥，或者在油壓源上進行流量控制。

NOTE

If the flow volume of the incoming pressure side is too much, there is a possibility that the proper sequential procedures would not work. In this instance, use a flow control valve to adjust flow volume from the pressure source.

訂購標示法 ORDERING INDICATION

示例: CLG-3A(5.0MPa)

CLG	系列 Series	CLG
3	順序動作壓力調整範圍 Sequential action pressure adjustment range	3: 1.0~6.0 MPa 6: 5.0~18.0MPa
A	A油路板型式	A Manifold type
5.0MPa	設定壓力 (順序動作壓力的設定值) Set pressure(Set valve for sequence operating pressure)	1.使用壓力與設定壓力的壓差應設定在1MPa以上。 2.多台順序閥並聯於迴路中使用時，相互間設定壓力的壓差應在1MPa以上。 Provide a difference of more than 1MPa between operating and setting pressure. When using multiple CLG sequence valves in a parallel fashion, provide each set pressure with a pressure difference more than 1MPa.

規格參數表 SPECIFICATION

型號	順序動作壓力調整範圍	使用壓力範圍	調節螺釘壓力變化值 (MPa/每圈)	開啟壓力	使用溫度	使用流體
MODEL	SEQUENTIAL ACTION PRESSURE ADJUSTMENT RANGE(MPa)	OPERATING PRESSURE RANGE(MPa)	ADJUSTING SCREW TURN RATIO(MPa/REV)	CRACKING PRESSURE (MPa)	OPERATING TEMPERATURE(°C)	USABLE FLUID
CLG-3A	1.0~6.0	2.0~35.0	1.0	0.01	0~70°C	相當於ISO黏度等級的ISO-VG-32一般液壓油General Hydraulic Oil Equivalent to ISO-VG-32
CLG-6A	5.0~18.0	6.0~35.0	2.8	0.01	0~70°C	

